

IN THE CLAIMS

Claim 1 (Currently Amended): An apparatus comprising:
a first and a second light fixture coupling bracket each adapted to removably couple to a frame of a light box, the first and the second light fixture coupling brackets each including a first and a second through-hole and coupled to the frame by a light bar coupling device inserted into the first through-hole of the first and the second light fixture coupling brackets,
a first and a second tightening handle each coupled to a light fixture coupling bracket through the second through-hole of the first and the second light fixture coupling brackets,
wherein said light bar coupling device bracket includes including an attaching pin to couple to a light bar having at least one socket adapted to accept the attaching pin within the at least one socket, said plurality of light fixture coupling brackets adaptable to couple to a removably and adjustable gripping device including a gripping pin, said gripping device is rotatably adjusted around said light box, said gripping device coupled with the first and the second tightening handles and the first and the second light fixture coupling brackets, and the attaching pin is coupled to a bracket coupler that is slidably coupled in a groove in the light bar bracket.

Claim 2 (Canceled)

Claim 3 (Previously Presented): The apparatus of claim 1, said adjustable gripping device further including:

a gripping pin coupled to a rear portion of said gripping device, the first and a second tightening handle opposing one another, wherein said first and said second tightening handle adjusts an angle of said adjustable gripping device in relation to of the first and the second light fixture coupling brackets and the light box, said gripping pin is substantially centered on said rear portion.

Claim 4 (Currently Amended): The apparatus of claim 1, of the first and the second light fixture coupling brackets each being adaptable to couple to a light bar bracket having at least one light set attaching pin, wherein said at least one light attaching pin couples to a removable light set.

Claim 5 (Currently Amended): An apparatus comprising:

a light bar having at least one socket adapted that to attaches to an attaching pin, the light bar coupled to a light bar bracket, the attaching pin to couples to the at least one socket through insertion into the at least one socket, said light bar including at least one removable gripping device, said gripping device including a gripping pin substantially centered on a rear portion of said light bar, said gripping pin is removable from said gripping device, said gripping device is removably coupled to a plurality of light fixture coupling brackets through a first and a second tightening handle, wherein said removable gripping device is removably coupled to a light box having a plurality of expansion rods coupled to a first and a second frame, and each of a plurality of light fixture coupling devices is removably coupled through the light bar and through the plurality of light fixture coupling brackets, and the attaching pin is coupled to a bracket coupler that is coupled in a groove in a light bar bracket.

Claim 6 (Previously Presented): The apparatus of claim 5, wherein said light bar includes at least one light set attaching pin, wherein said at least one light set attaching pin couples to a removable light set bracket.

Claim 7 (New): The apparatus of claim 1, further comprising:

a second attaching pin to couple to the light bar, wherein the light bar having another socket.